



**Schäfer + Peters GmbH**  
Competence in Stainless Steel



WINDOW FRAME SCREWS, HEAD Ø 7,5 AND 11 MM,  
ARTICLE 9008 - 9009 TX



# ARTICLE 9008 - 9009 TX WINDOW FRAME SCREWS HEAD Ø 7,5 AND 11 MM

## PRODUCT ADVANTAGES:

- Fast and safe installation in various surfaces
- No pulling force between cover frame and masonry
- Can be used without dowels in the masonry
- optimal torque transmission
- no „come-out“ effect of the bit

## USES:

Mounting screw for window and door frames made of wood, metal or plastic in various surfaces.

## drilling diameter:

over frame: 6,5 mm

concrete: 6,5 mm

other masonry: 6,0 mm

cellular concrete: no pre-drilling necessary

## drilling depths:

Mind. 30 mm = concrete

Mind. 40 mm = lime stone

Mind. 50 mm = pumice stone

Mind. 60 mm = lightweight concrete, vertical coming brick

## FEATURES:

- full thread (except length 212 mm)

- head diameter 7.5 mm:

Socket head

- head diameter 11 mm:

small countersunk head

## MATERIAL CLASSIFICATION:

Austenitic stainless and anti-corrosion special-grade steel for use in damp rooms and outdoor applications without significant levels of chlorides or sulfuric acid.

## Article 9008 A2 TX

### Window frame screw - Head Ø 11 mm

d d	l l	k k	dk dk	b b	b1 b1	Antrieb Drive size	Artikelnummer Item Number	
7,5	40	2,6	11	-	-	TX30	9008275 40	100
	60	2,6	11	-	-	TX30	9008275 60	100
	80	2,6	11	-	-	TX30	9008275 80	100
	100	2,6	11	-	-	TX30	9008275 100	100
	120	2,6	11	-	-	TX30	9008275 120	100
	132	2,6	11	-	-	TX30	9008275 132	100
	150	2,6	11	-	-	TX30	9008275 150	100
	180	2,6	11	-	-	TX30	9008275 180	100
	212	2,6	11	137	40	TX30	9008275 212	100

## Article 9009 A2 TX

### Window frame screw - Head Ø 7,5 mm

d d	l l	k k	dk dk	b b	b1 b1	Antrieb Drive size	Artikelnummer Item Number	
7,5	40	3	8	-	-	TX30	9009275 40	100
	60	3	8	-	-	TX30	9009275 60	100
	80	3	8	-	-	TX30	9009275 80	100
	100	3	8	-	-	TX30	9009275 100	100
	120	3	8	-	-	TX30	9009275 120	100
	132	3	8	-	-	TX30	9009275 132	100
	150	3	8	-	-	TX30	9009275 150	100
	180	3	8	-	-	TX30	9009275 180	100
	212	3	8	137	40	TX30	9009275 212	100

